

# GNU make cheat sheet

Nasser M. Abbasi

October 27, 2025

Compiled on October 27, 2025 at 12:37am

## Contents

1	recursive make	1
2	using common.mk in recursive make	2
3	How to build a file in the current directory without traversing the whole tree?	2
4	Using -,+,@ before SHELL commands	3
5	How to find number of column and rows on Linux terminal?	3
6	Links	3

## 1 recursive make

Assume this tree structure

```
A-----B
 |
+---C
```

Recursive make can be used to build everything in the tree. The directory `$HOME` contains this `common.mk` file

```
all::
    @for d in $(DIRS); \
    do \
        $(MAKE) --directory=$$d; \
    done
```

Each of the subdirectories will contain a Makefile that includes the `common.mk`. Then running the command `make -I$HOME` from A gives

```
>make
make[1]: Entering directory `/tmp/B'
make[1]: Leaving directory `/tmp/B'
make[1]: Entering directory `/tmp/C'
make[1]: Leaving directory `/tmp/C'
```

## 2 using common.mk in recursive make

Following from the above, each Makefile in subfolders will start by defining its own specific variables, and then it will include a `common.mk` which resides in common location such as `$HOME`.

Each makefile will include this file. An example of a Makefile in the A directory shown above is

```
DIRS:= B C
include common.mk
all::
```

Each sub directory will include similar makefile which starts by listing the directories below it, then including `common.mk`

The actions actually performed by makefile will be done at the bottom most directories first, followed by the higher level up. This means the tree is first traversed to the bottom, then when the bottom is reached, on going back up, each makefile will execute any other action in its `all` such as compiling files and other such tasks. So, this is like a stack. The last directory visited on the way down, is the first directory that will be updated in the build process, and the top directory, will be the last directory that is updated.

## 3 How to build a file in the current directory without traversing the whole tree?

Suppose I have `index.tex` that I want to build it to `index.htm` to try something but it is already up to date. But if I do `make clean` it will now clean everything down the whole tree, which is not what I want.

I can touch `index.tex` then do `make`. But I can also use `-B` option and give it the target to build, like this

```
make -I$HOME -B index.htm
```

## 4 Using -,+,@ before SHELL commands

from <http://pic.dhe.ibm.com/infocenter/aix/v6r1/> it says

@	Causes the command not to be echoed before it is executed.
-	Causes any nonzero exit status of the command line to be ignored.
+	Causes a command line to be executed, even though the options -n, -q, or -t are specified.

## 5 How to find number of column and rows on Linux terminal?

```
echo -e "lines\ncols" | tput -S | ref: this also stty size
```

Tools for terminal are here

## 6 Links

Has make build-in symbols [http://www.chemie.fu-berlin.de/chemnet/use/info/make/make\\_15.html](http://www.chemie.fu-berlin.de/chemnet/use/info/make/make_15.html)